## Approved For Release 2002/06/11: CIA-RDP67B00820R000400040002-6

**		DIECH	DDSar	
			6a	
		DFA		
· PIRECTOR		1 00	2.4:	
NOM:	25X1A	commo	1 1 100 mm on the control of the con	
CTION:		ROUTINE	A STATE OF THE PROPERTY OF THE	
FO:		1) of U 1 L 1 V 1		
TOR 0408Z 13 NOV 64		- Seculor seculos	The second secon	
25X1A 25X	ر سر سر (۱۸ × ۱۸ × ۱۸ × ۱۸ ×		IN 57404	
A CONTROL OF THE PROPERTY OF T	CBA 1-15 E		A.A. L. No. Com-	
PRIORITY		OFFE	8784 25X1	
OXCART			<sup>8784</sup> 25X1/	
NO NITE ACTION				
	N. W			
PRELIMINARY Q BAY PACKA	GE TEST REPORT			
I. GENERAL				
lo TYPE I.				
2. TEST NO. ATF-8:	C.			
3. TEST DATE 5 NOV	64.			
4. ARTICLE NO. 12	3 .			
S. Time: T.O. 16.	402 LAND 20402,			
	TINE: 40 MINUTES TOTA	Y EXTRUTE 1 701	9(조)	
AND 20162.		them that have do 197 have been \$150 m. It is is to be	) i	
T. TEST CONDITIONS				
	•			
A. PRESS ALT 72				
B. BAOM NO. 2.2				
Co I.N.S. STATE				
D. WEATHER: OC	OD			
8. TEST OBJECTIVES:	TASK 1060 - CHECK HEL	IUM CONSUMPTIO	N	

Approved For Release 2002/06/11: CIA-RDP67B00820R000400040002-6
REPRODUCTION BY OTHER THAN THE ISSUING OFFICE IS PROHIBITED. Gary No.

25X1A

8704 (IN 57404) SEORET

PAGE TWO

AT ALTITUDE. 1053 - CONFIRM PROPER OF BALANCE. 1047, 1028 CHECK FOR GHOSTING. 1064 FOCUS ON FORWARD BENCH. 1044 V/H SCALING. 1001, 1055 ATMOSPHERIC STUDY WITH WHITE CARDS. 106, 107 CONFIRM MAG RECORDER TAKES 6 DATA OUTPUTS PER SPECS.

- 9. TEST RESULTS: 1060 HELIUM CONSUMPTION: 266 GMS OVER
  43 MINS EQUALS 6.3 GMS PER MIN. 1053 CG BALANCE NO CONCLUSIONS
  DUE TO GYRO NOISE AND ROUGH FLIGHT. 1047, 1029 GHOSTING NO
  GHOSTING NOTICED ON ANY FRAMES. 1064 FOCUS NO CONCLUSIONS
   NO TARGETS. 1044 V/H SCALING RAN IN CL DUE TO WX FORECAST.
  CLOUD SET APPROX 1 PERCENT LOW FOR 35 MR. 106, 107 MAG RECORDER
  OPERATED BY US IN STDBY 1. DATA SCAN VERY ERRATIC. A ONE TO SIX
  SECS PER SCAN. NO COORDINATION WITH DATA CHAMBER DUE TO REMOVAL
  OF PLUE 96 PRIOR TO FLIGHT TO ELIMINATE INTERFACE PROBLEM.
- 10. COMMENTS: SYSTEM LOST PHASING DURING LAST PORTION OF FLIGHT. LAST PORTION FLOWN WITH SYSTEM CAGED DUE TO LOW ANGLE OF ATTACK. WHEN SYSTEM WAS GIVEN POST FLIGHT THE SCANNERS WOULD NOT SYC AND THE TAKE UP STARTED IN REVERSE. FURTHER INVESTIGATION OF THIS PHENOMENON WILL BE CONDUCTED WHEN VEHICLE IS AVAILABLE FOR TEST. SYSTEM PERFORMED SATISFACTORILY IN LABORATORY. NO ATMOSPHERIC DATA TAKEN SINCE TEST WAS ABORTED PRIOR TO PASSING OVER TARGETS.

END OF MESSAGE